

Infrastructure description

As at: 01/01/2013

KTL
Kombi- Terminal Ludwigshafen GmbH
Am Hansenbusch 11
67069 Ludwigshafen

Rail infrastructure

Railway operator within the transshipment facility:

BASF SE, 67056 Ludwigshafen – Contact via info@ktl-lu.de or Tel. 0621/65913-0

Number of loading sidings:	Module 10: 3	Module 20: 4	Module 30: 6
Length of siding:	Module 10: 620 m	Module 20: 560 m	Module: 30: 620m
Number of storage sidings:	13		
Length of siding:	600 – 800 meter		
Electrification:	10 storage sidings and the ends of all loading sidings; Entrance with e-locs possible for all loading sidings		

Road infrastructure

Check-in queuing area:	Around 12- 15 (depending on length of vehicle)		
Check in-system:	1- 4 lanes		
Car park entrance:	32		
Number of truck loading lanes:	Module 10: 1	Module 20: 1	Module 30: 2
Length of truck loading lanes:	Module 10: 620 m	Module 20: 560 m	Module 30: 620 m

Transshipment facility infrastructure

Number of handling cranes:	Module 10: 2	Module 20: 2	Module 30: 3
Number of mobile equipment:	2 (only in the depot)		
Load bearing capacity of crane:	38 – 42 tonnes		
Storage lanes:	Module 10: 2	Module 20: 2 + 2	Module 30: 6
Storage area capacity (TEU); (Occupancy rate 70%):	Module 10: 450	Module 20: 600	Module 30: 1260